

GALVEST ALL PURPOSE WHITE

Permanent Whitewash

COATINGS

WHITEWASH

MANUFACTURER:

Empire Blended Products, Inc.
250 Hickory Lane • Bayville, NJ 08721
(732) 269-4949 • Fax (732) 269-0497

PRODUCT DESCRIPTION:

GALVEST ALL PURPOSE WHITE is an economical, permanent, all purpose coating designed for both interior and exterior unpainted surfaces. It dries to a brilliant, flat white finish and is ideal for use over unpainted brick, stone, cinder block, concrete block and all other cement surfaces.

USES:

- ▶ Interior and exterior unpainted concrete and masonry surfaces
- ▶ Walls and ceilings
- ▶ Cellar walls, foundations, curbs and garages
- ▶ Factories, warehouses, barns and stables



ADVANTAGES:

- ▶ Very economical to use
- ▶ Can be applied by brush, roller or sprayer
- ▶ Provides a permanent coating
- ▶ Easily washable
- ▶ Maintains brilliant appearance for many years
- ▶ Covers in one coat
- ▶ Will not peel or rub off
- ▶ Quick drying

INSTALLATION:

Surface Preparation:

All surfaces to be coated must be free of loose dirt, debris, paints, oils and other contaminants that will prevent proper bond. *GALVEST ALL PURPOSE*



WHITE can not be applied over previously painted surfaces unless paint is removed by sandblasting, waterblasting or other method. Completely dampen surfaces to be coated and make certain surface stays damp ahead of application.

Mixing:

In a clean container, add *GALVEST ALL PURPOSE WHITE* to clean water in the ratio of 5 pounds of *GALVEST ALL PURPOSE WHITE* for every 3 quarts of water. Stir thoroughly until powder is completely dissolved.

Placement:

GALVEST ALL PURPOSE WHITE can be applied by brush, roller or sprayer. Apply material liberally working it into the pores of the surface to ensure one coat coverage. If a second coat is desired, allow material to dry 2 hours before next application.

Curing:

GALVEST ALL PURPOSE WHITE is self-curing. Allow to dry for 12 hours before washing surface.

Coverage:

Each 5 pounds of *GALVEST ALL PURPOSE WHITE* will mix to yield 1 gallon and will cover approximately 100 square feet of rough surface area.

Packaging:

Available in 10 pound bags (5 per carton) and 25 pound bags (2 per carton).

Color:

White

TECHNICAL DATA:

Drying Time. 12 hours

LIMITATIONS:

Do not use on surfaces that have been previously painted. Do not apply to frozen surfaces or if temperature will fall below 40°F within 12 hours.

CAUTION:

Contains Lime CAS #1305-62-0. May cause irritation of the eyes, skin or respiratory tract. Avoid creating excessive dust levels. Use with adequate ventilation.
Avoid contact with skin

where possible and wash exposed areas promptly with water. If any product gets into the eye, rinse immediately and repeatedly with water and seek prompt medical attention. If ingested, **do not** induce vomiting and get prompt medical attention. If dust levels are excessive, tight fitting goggles, rubber gloves, long sleeve clothing, pants tucked into boots and NIOSH approved respiratory protection are recommended. **Keep Out Of Reach Of Children.**

WARRANTY:

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either Empire Blended Products or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.